

















KOMFORT EC DBE

Suspended heat recovery air handling units



- Heat exchanger type: Counter flow, Cross flow
- Heat exchanger material: Polystyrene, Enthalpy, Aluminum
- Sound-insulated casing
- Bypass: Auto
- BMS protocol: ModBus
- CO2 sensor: Optional
- PM2.5 sensor: Optional

Lineup	Connected air duct size, mm	Rated power, W	Service side	Control system	Preheater	Reheater	BMS protocol	Number of speeds
 KOMFORT EC DBE 300 R S21 DTV	160	180	Right	S21	Optional	Electric	ModBus	1
 KOMFORT EC DBE 300 L S21 DTV	160	180	Left	S21	Optional	Electric	ModBus	1
 KOMFORT EC DBE 300-E R S21 DTV	160	180	Right	S21	Optional	Electric	ModBus	1
 KOMFORT EC DBE 300-E L S21 DTV	160	180	Left	S21	Optional	Electric	ModBus	1
 KOMFORT EC DBE 550 R S21 DTV	200	322	Right	S21	Optional	Electric	ModBus	1
 KOMFORT EC DBE 550 L S21 DTV	200	322	Left	S21	Optional	Electric	ModBus	1
 KOMFORT EC DBE 550-E R S21 DTV	200	322	Right	S21	Optional	Electric	ModBus	1

	KOMFORT EC DBE 550-E L S21 DTV	200	322	Left	S21	Optional	Electric	ModBus	1
	KOMFORT EC DBE 900 R S21 DTV	250	442	Right	S21	Optional	Electric	ModBus	1
	KOMFORT EC DBE 900 L S21 DTV	250	442	Left	S21	Optional	Electric	ModBus	1
	KOMFORT EC DBE 900-E R S21 DTV	250	442	Right	S21	Optional	Electric	ModBus	1
	KOMFORT EC DBE 900-E L S21 DTV	250	442	Left	S21	Optional	Electric	ModBus	1
	KOMFORT EC DBE 2000 S21 DTV	315	1063	Right	S21	✘	Electric	ModBus	1
	KOMFORT EC DBE 2000 S21	315	1063	Right	S21	✘	Electric	ModBus	1
	KOMFORT EC DBE 3000 S21 DTV	400	2226	Right	S21	✘	Electric	ModBus	1
	KOMFORT EC DBE 3000 S21	400	2226	Right	S21	✘	Electric	ModBus	1