

KOMFORT EC DBE

Suspended heat recovery air handling units

- Heat exchanger type: Counter flow, Cross flow
- Heat exchanger material: Polystyrene, Enthalpy, Aluminum
- Sound-insulated casing
- Bypass: Auto
- BMS protocol: ModBus
- Casing material: Galvanized steel
- Humidity sensor: Optional
- CO2 sensor: Optional
- PM2.5 sensor: Optional

Lineup	Connected air duct size, mm	Phases	Maximum airflow, m³/h	Service side	Control system	Reheater	Preheater	BMS protocol
KOMFORT EC DBE 300 R S21 DTV	160	1	340	Right	S21	Electric	Optional	ModBus
KOMFORT EC DBE 300 L S21 DTV	160	1	340	Left	S21	Electric	Optional	ModBus
KOMFORT EC DBE 300-E R S21 DTV	160	1	340	Right	S21	Electric	Optional	ModBus
KOMFORT EC DBE 300-E L S21 DTV	160	1	340	Left	S21	Electric	Optional	ModBus
KOMFORT EC DBE 550 R S21 DTV	200	1	608	Right	S21	Electric	Optional	ModBus
KOMFORT EC DBE 550 L S21 DTV	200	1	608	Left	S21	Electric	Optional	ModBus
KOMFORT EC DBE 550-E R S21 DTV	200	1	608	Right	S21	Electric	Optional	ModBus

 KOMFORT EC DBE 550-E L S21 DTV	200	1	608	Left	S21	Electric	Optional	ModBus
 KOMFORT EC DBE 900 R S21 DTV	250	1	1030	Right	S21	Electric	Optional	ModBus
 KOMFORT EC DBE 900 L S21 DTV	250	1	1030	Left	S21	Electric	Optional	ModBus
 KOMFORT EC DBE 900-E R S21 DTV	250	1	1030	Right	S21	Electric	Optional	ModBus
 KOMFORT EC DBE 900-E L S21 DTV	250	1	1030	Left	S21	Electric	Optional	ModBus
 KOMFORT EC DBE 2000 S21 DTV	315	3	2100	Right	S21	Electric	✖	ModBus
 KOMFORT EC DBE 2000 S21	315	3	2100	Right	S21	Electric	✖	ModBus
 KOMFORT EC DBE 3000 S21 DTV	400	3	4300	Right	S21	Electric	✖	ModBus
 KOMFORT EC DBE 3000 S21	400	3	4300	Right	S21	Electric	✖	ModBus