











KOMFORT EC DBW

Suspended heat recovery air handling units



- Heat exchanger type: Cross flow
- Sound insulation
- Motor type: EC
- Bypass: Auto
- Reheater: Water
- Preheater: Optional
- BMS protocol: ModBus
- Control: Smartphone
- Casing material: Galvanized steel
- Humidity sensor: Optional
- Enthalpy heat exchanger

Lineup	Connected air duct size, mm	Speed	Phases	Maximum supply voltage, V	Heat recovery efficiency, max, %	Heat exchanger material	Extract filter	Supply filter	Service side	Control system	Reheater	Preheater	BMS protocol
 KOMFORT EC DBW 550 R S21 DTV	200	1	1	230	90	Polystyrene	G4	G4 (опция: F7)	Right	S21	Water	Optional	ModBus
 KOMFORT EC DBW 550 L S21 DTV	200	1	1	230	90	Polystyrene	G4	G4 (F7 option)	Left	S21	Water	Optional	ModBus
 KOMFORT EC DBW 550-E R S21 DTV	200	1	1	230	87	Enthalpy	G4	G4 (F7 option)	Right	S21	Water	Optional	ModBus
 KOMFORT EC DBW 550-E L S21 DTV	200	1	1	230	87	Enthalpy	G4	G4 (опция: F7)	Left	S21	Water	Optional	ModBus
 KOMFORT EC DBW 900 R S21 DTV	250	1	1	230	88	Polystyrene	G4	G4 (F7 option)	Right	S21	Water	Optional	ModBus
 KOMFORT EC DBW 900 L S21 DTV	250	1	1	230	88	Polystyrene	G4	G4 (F7 option)	Left	S21	Water	Optional	ModBus
 KOMFORT EC DBW 900-E R S21 DTV	250	1	1	230	85	Enthalpy	G4	G4 (F7 option)	Right	S21	Water	Optional	ModBus
 KOMFORT EC DBW 900-E L S21 DTV	250	1	1	230	85	Enthalpy	G4	G4 (F7 option)	Left	S21	Water	Optional	ModBus
 KOMFORT EC DBW 2000 S21 DTV	315	1	1	230	67	Aluminum	G4	G4 (F7 option)	Right	S21	Water	✗	ModBus

	KOMFORT EC DBW 3000 S21 DTV	400	1	3	400	72	Aluminum	G4	G4 (F7 option)	Right	S21	Water	✕	ModBus
---	-----------------------------	-----	---	---	-----	----	----------	----	----------------	-------	-----	-------	---	--------