









# KOMFORT ERV EC DB

Suspended heat and energy recovery air handling units



- Heat exchanger type: Cross flow
- Sound insulation
- Motor type: EC
- Enthalpy heat exchanger
- Bypass: Manual
- Control: Wired control panel
- Casing material: Coated steel
- Humidity sensor: Optional

Lineup	Rated power, W	Maximum airflow, m <sup>3</sup> /h	Sound pressure level LpA at 3 m, dB(A)	Heat recovery efficiency, max, %	Service side	Control system	Bypass
 KOMFORT ERV EC DB 100 R S14	66	170	30	82	Right	S14	✓
 KOMFORT ERV EC DB 100 L S14	66	170	30	82	Left	S14	✓
 KOMFORT ERV EC DB 150 R S14	83	215	32	82	Right	S14	✓
 KOMFORT ERV EC DB 150 L S14	83	215	32	82	Left	S14	✓
 KOMFORT ERV EC DB 250 R S14	84	300	36	73	Right	S14	✓
 KOMFORT ERV EC DB 250 L S14	84	300	36	73	Left	S14	✓

 KOMFORT ERV EC DB 350 R S14	171	430	46	85	Right	S14	✓
 KOMFORT ERV EC DB 350 L S14	171	430	46	85	Left	S14	✓