











# KOMFORT Roto EC DE S21

Suspended heat recovery air handling units

- Heat exchanger type: Rotary
- Heat exchanger material: Aluminum
- Sound-insulated casing
- BMS protocol: ModBus
- CO2 sensor: Optional
- PM2.5 sensor: Optional



Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m <sup>3</sup> /h	Service side	Control system	Reheater	BMS protocol	Article
 KOMFORT Roto EC D2E 250 R S21	160	128	300	Right	S21	Electric	ModBus	8065729
 KOMFORT Roto EC DE 250 R S21	160	135	310	Right	S21	Electric	ModBus	8065699
 KOMFORT Roto EC D2E 350 R S21	160	200	400	Right	S21	Electric	ModBus	8066030
 KOMFORT Roto EC DE 350 R S21	160	185	430	Right	S21	Electric	ModBus	8065996
 KOMFORT Roto EC DE 650 R S21	200	367	710	Right	S21	Electric	ModBus	8069055
 KOMFORT Roto EC D2E 250 L S21	160	128	300	Left	S21	Electric	ModBus	8065231
 KOMFORT Roto EC DE 250 L S21	160	135	310	Left	S21	Electric	ModBus	8065682

 KOMFORT Roto EC D2E 350 L S21	160	200	400	Left	S21	Electric	ModBus	8066023
 KOMFORT Roto EC DE 350 L S21	160	185	430	Left	S21	Electric	ModBus	8065989
 KOMFORT Roto EC DE 650 L S21	200	367	710	Left	S21	Electric	ModBus	8069048