











KOMFORT Roto EC DE S21

Suspended heat recovery air handling units



- Heat exchanger type: Rotary
- Sound insulation
- Motor type: EC
- Reheater: Electric
- BMS protocol: ModBus
- Control: Smartphone
- Casing material: Galvanized steel
- Humidity sensor: Optional

Lineup	Connected air duct size, mm	Speed	Power of electrical reheater, W	Maximum airflow, m ³ /h	Sound pressure level LpA at 3 m, dB(A)	Heat recovery efficiency, max, %	Extract filter	Supply filter	Service side	Control system	Reheater	BMS protocol
 KOMFORT Roto EC D2E 250 R S21	160	1	700	300	23	87	G4	G4	Right	S21	Electric	ModBus
 KOMFORT Roto EC DE 250 R S21	160	1	700	310	21	87	G4	G4	Right	S21	Electric	ModBus
 KOMFORT Roto EC D2E 350 R S21	160	1	1400	400	33	87	G4	G4	Right	S21	Electric	ModBus
 KOMFORT Roto EC DE 350 R S21	160	1	1400	430	31	87	G4	G4	Right	S21	Electric	ModBus
 KOMFORT Roto EC DE 650 R S21	200	1	2800	710	36	87	G4	G4	Right	S21	Electric	ModBus
 KOMFORT Roto EC D2E 250 L S21	160	1	700	300	23	87	G4	G4	Left	S21	Electric	ModBus
 KOMFORT Roto EC DE 250 L S21	160	1	700	310	21	87	G4	G4	Left	S21	Electric	ModBus
 KOMFORT Roto EC D2E 350 L S21	160	1	1400	400	33	87	G4	G4	Left	S21	Electric	ModBus
 KOMFORT Roto EC DE 350 L S21	160	1	1400	430	31	87	G4	G4	Left	S21	Electric	ModBus

	KOMFORT Roto EC DE 650 L S21	200	1	2800	710	36	87	G4	G4	Left	S21	Electric	ModBus
---	------------------------------	-----	---	------	-----	----	----	----	----	------	-----	----------	--------