













KOMFORT Roto EC L(E)HP

Compact heat recovery air handling units



- Heat exchanger type: Rotary
- Sound insulation
- Motor type: EC
- Control: Wired control panel
- Casing material: Aluzinc steel
- Humidity sensor: Optional
- Preheater: Built-in

Lineup	Connected air duct size, mm	Speed	Phases	Maximum supply voltage, V	Maximum airflow, m ³ /h	Sound pressure level LpA at 3 m, dB(A)	Heat exchanger material	Extract filter	Supply filter	Service side	Control system	Frost protection	Preheater
 KOMFORT Roto EC LHP 400 S17	160	1	1	230	520	45	Aluminum	G4	G4 (option: F7)	Right	S17	Rotor rotation control	✗
 KOMFORT Roto EC LHP 400 S18	160	1	1	230	520	45	Aluminum	G4	G4 (option: F7)	Right	S18	Rotor rotation control	✗
 KOMFORT Roto EC LEHP 400 S17	160	1	1	230	520	45	Aluminum	G4	G4 (option: F7)	Right	S17	Preheating	Built-in
 KOMFORT Roto EC LEHP 400 S18	160	1	1	230	520	45	Aluminum	G4	G4 (option: F7)	Right	S18	Preheating	Built-in
 KOMFORT Roto EC LHP 700 S17	250	1	1	230	830	52	Aluminum	G4	G4 (option: F7)	Right	S17	Rotor rotation control	✗
 KOMFORT Roto EC LHP 700 S18	250	1	1	230	830	52	Aluminum	G4	G4 (option: F7)	Right	S18	Rotor rotation control	✗
 KOMFORT Roto EC LEHP 700 S17	250	1	1	230	830	52	Aluminum	G4	G4 (option: F7)	Right	S17	Preheating	Built-in
 KOMFORT Roto EC LEHP 700 S18	250	1	1	230	830	52	Aluminum	G4	G4 (option: F7)	Right	S18	Preheating	Built-in
 KOMFORT Roto EC LHP 900 S17	250	1	1	230	955	58	Aluminum	G4	G4 (option: F7)	Right	S17	Rotor rotation control	✗

	KOMFORT Roto EC LHP 900 S18	250	1	1	230	955	58	Aluminum	G4	G4 (option: F7)	Right	S18	Rotor rotation control	✕
	KOMFORT Roto EC LEHP 900 S17	250	1	1	230	955	58	Aluminum	G4	G4 (option: F7)	Right	S17	Preheating	Built-in
	KOMFORT Roto EC LEHP 900 S18	250	1	1	230	955	58	Aluminum	G4	G4 (option: F7)	Right	S18	Preheating	Built-in