







KOMFORT Roto EC SE

Heat recovery air handling units

- Heat exchanger type: Rotary
- Sound insulation
- Motor type: EC
- Reheater: Electric
- BMS protocol: ModBus
- Control: Smartphone
- Casing material: Coated steel
- Humidity sensor: Optional

| Lineup | Connected air duct size, mm | Power of electrical reheater, W | Maximum airflow, m ³ /h | Sound pressure level LpA at 3 m, dB(A) | Heat recovery efficiency, max, % | Service side | Control system | Reheater | BMS protocol |
|---|-----------------------------|---------------------------------|------------------------------------|--|----------------------------------|--------------|----------------|----------|--------------|
|  KOMFORT Roto EC S2E 200 S21 | 125 | 700 | 270 | 28 | 92 | Universal | S21 | Electric | ModBus |
|  KOMFORT Roto EC SE 280 S21 | 125 | 650 | 300 | 26 | 90 | Universal | S21 | Electric | ModBus |
|  KOMFORT Roto EC SE 400 S21 | 160 | 1400 | 440 | 33 | 85 | Universal | S21 | Electric | ModBus |
|  KOMFORT Roto EC SE 600 S21 | 200 | 2800 | 670 | 35 | 89 | Universal | S21 | Electric | ModBus |