











# KOMFORT Roto EC SKE 200

Air handling units with rotary heat exchanger

- Heat exchanger type: Rotary
- Sound insulation
- Motor type: EC
- Bypass: Auto
- BMS protocol: ModBus
- Control: Smartphone
- Casing material: Steel
- Humidity sensor: Optional
- Reheater: Built-in

Lineup	Connected air duct size, mm	Maximum airflow, m <sup>3</sup> /h	Sound pressure level LpA at 3 m, dB(A)	Heat recovery efficiency, max, %	Extract filter	Supply filter	Service side	Control system	BMS protocol	Power of electrical reheater, W	Reheater
 KOMFORT Roto EC SK 200 L S21	125	270	33	93	G4	G4 (опция: F7)	Left	S21	ModBus		
 KOMFORT Roto EC SK 200 R S21	125	270	33	93	G4	G4 (опция: F7)	Right	S21	ModBus		
 KOMFORT Roto EC SKS 200 L S21	125	270	33	93	G4	G4 (опция: F7)	Left	S21	ModBus		
 KOMFORT Roto EC SKS 200 R S21	125	270	33	93	G4	G4 (опция: F7)	Right	S21	ModBus		
 KOMFORT Roto EC SKE 200 L S21	125	270	33	93	G4	G4 (опция: F7)	Left	S21	ModBus	700	Built-in
 KOMFORT Roto EC SKE 200 R S21	125	270	33	93	G4	G4 (опция: F7)	Right	S21	ModBus	700	Built-in
 KOMFORT Roto EC SKES 200 L S21	125	270	33	93	G4	G4 (опция: F7)	Left	S21	ModBus	700	Built-in
 KOMFORT Roto EC SKES 200 R S21	125	270	33	93	G4	G4 (опция: F7)	Right	S21	ModBus	700	Built-in