






















## Trio

Low noise and low power extract axial fan

- Motor type: AC
- Casing material: Plastic
- Timer: Turn off timer, Turn on timer
- Humidity sensor

Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m <sup>3</sup> /h	Sound pressure level LpA at 3 m, dB(A)	Pull cord	Timer	Humidity sensor
 Trio 100	100	8	90	29			
 Trio 100 S	100	8	90	29	✓		
 Trio 100 T	100	8	90	29		✓	
 Trio 100 TR	100	8	90	29		✓	
 Trio 100 ST	100	8	90	29	✓	✓	
 Trio 100 H	100	8	90	29		✓	✓

 Trio 100 SH	100	8	90	29	✓	✓	✓
 Trio 150	150	28	255	35			
 Trio 150 S	150	28	255	35	✓		
 Trio 150 T	150	28	255	35		✓	
 Trio 150 TR	150	28	255	35		✓	
 Trio 150 ST	150	28	255	35	✓	✓	
 Trio 150 H	150	28	255	35		✓	✓
 Trio 150 SH	150	28	255	35	✓	✓	✓
 Trio V2 100	100	8	81	28			
 Trio V2 100 TR	100	8	81	28		✓	
 Trio V2 100 H	100	8	81	28		✓	✓
 Trio V2 150	150	21	300	35			
 Trio V2 150 TR	150	21	300	35		✓	

	Trio V2 150 H	150	21	300	35		✓	✓
---	---------------	-----	----	-----	----	--	---	---