















Valeo-E

Mono-pipe ventilation exhaust centrifugal fans

- Control: Wired control panel
- Casing material: Plastic
- Timer: Built-in
- Motion sensor
- Humidity sensor: Built-in

Lineup	Connected air duct size, mm	Maximum airflow, m ³ /h	Sound pressure level LpA at 3 m, dB(A)
 Valeo-E 35/60	80	63	36
 Valeo-E 35/60 K	80	63	36
 Valeo-E 35/60 T	80	63	36
 Valeo-E 35/60 TR	80	63	36
 Valeo-E 35/60 I	80	63	36
 Valeo-E 35/60 H	80	63	36
 Valeo-E 35/60 K T	80	63	36

 Valeo-E 35/60 K TR	80	63	36
 Valeo-E 35/60 K I	80	63	36
 Valeo-E 35/60 K H	80	63	36
 Valeo-E 75/100	80	100	38
 Valeo-E 75/100 K	80	100	38
 Valeo-E 75/100 T	80	100	38
 Valeo-E 75/100 TR	80	100	38
 Valeo-E 75/100 I	80	100	38
 Valeo-E 75/100 H	80	100	38
 Valeo-E 75/100 K T	80	100	38
 Valeo-E 75/100 K TR	80	100	38
 Valeo-E 75/100 K I	80	100	38
 Valeo-E 75/100 K H	80	100	38