

| | | | | | | |
|-------------------------------------------------------------|---------------------------|----|---------|---|-------|---|
| Trade mark | BLAUBERG | | | | | |
| Model | KOMFORT ERV EC DB 250 S14 | | | | | |
| Specific energy consumption (SEC), kWh/(m ² .a) | Cold | | Average | | Warm | |
| | -79,3 | A+ | -38,4 | A | -15 | E |
| Type of ventilation unit | Bidirectional | | | | | |
| Type of drive installed | Variable speed | | | | | |
| Type of heat recovery system | Regenerative | | | | | |
| Thermal efficiency of heat recovery, % | 70 | | | | | |
| Maximum flow rate, m ³ /h | 200 | | | | | |
| Electric power input, W | 76 | | | | | |
| Sound power level, dB(A) | 36 | | | | | |
| Reference flow rate, m ³ /s | 0,036 | | | | | |
| Reference pressure difference, Pa | 50 | | | | | |
| Specific power input (SPI), W/(m ³ /h) | 0,331 | | | | | |
| Control typology | Local demand control | | | | | |
| Maximum internal leakage rates, % | 2,7 | | | | | |
| Maximum external leakage rates, % | 2,7 | | | | | |
| Internet address | | | | | | |
| The annual electricity consumption (AEC), kWh electricity/a | Cold | | Average | | Warm | |
| | 175 | | 175 | | 175 | |
| The annual heating saved (AHS), kWh primary energy/a | Cold | | Average | | Warm | |
| | 8 371 | | 4 279 | | 1 935 | |